



DVR



SST-JES-Q3004M

4Ch. H.264 CIF @ Realtime DVR

Features

- H.264 compression ideal for saving HDD space
- Real time live display
- Live display, record, backup, playback and network access simultaneously
- Picture-in-picture monitoring and 2X to 8X digital zoom display
- Control methods: front panel, USB mouse, IR remote controller, client viewer
- Intuitive GUI for easy configuration and menu driven operation
- Pan / Tilt / Zoom camera control
- Data backup: USB devices, network
- Event triggered with email notification: motion detection, alarm, video loss
- Supports Internet Explorer with same GUI as DVR site
- Multi-language OSD
- Central Management System (CMS) supports up to 15 DVRs
- 3G/GPRS mobile phone monitoring
- 2 USB ports for mouse usage and backup *
- Dual streaming enhances the speed of network transmission
- Built-in VGA output up to 1024x768 resolution
- Individual setup of resolution, frame rate and video quality for each channel
- Still image snapshot
- AVI converter with time stamp

Specification

Model		SST-JES-Q3004M
Video	Input	4 CH input
	Output	Main x 1 / SPOT Output x 1, VGA
Monitoring	VGA Output	1024x768
	Display Screen	1 / 4
Recording	Compressed Mode	H.264
	Recording Mode	Manual, Schedule, Event(motion detection/sensor)
	Playback Mode	Smart Search by Time, Calendar and Event
	Playback Speed	fast forward/backward 2X/4X/8X/16X/32X/64X slow forward/backward 1/2X,1/4X,1/8X,1/16X play/pause
	Recording Resolution	720x480, 720x240, 360x240 (NTSC) / 720x576, 720x288, 360x288 (PAL)
	Recording Rate	D1: 60 / Half D1: 120 / CIF: 120 (NTSC) D1: 50 / Half D1: 100 /CIF: 100 (PAL)
Audio	Recording Quality	Highest, High, Normal, Basic, Below Basic
	Audio Input	4CH RCA, 0.5~1.4 Vp-p@20K Ohm
Alarm	Audio Output	1CH RCA
	Sensor	4 input / 1 output
	Motion Detection	16X12 (sensitivity 0~10)
	Pre-Alarm Recording	16MB (10 sec)
Other Function	Post-Alarm Recording	1-999 sec
	Network Software	Internet Explorer / CMS / 3G Mobile Phone
	Network Users	5
	Backup	USB flash driver / Network
	Storage	SATA HDD x 1 (Max. 1TB)
	DVD Writer	-
	RS485	Pan / Tilt / Zoom camera
	Remote Notification	Email message
	Service	TCP/IP, SMTP, DHCP, DDNS, PPPoE
	Password	5 users including 1 administrator user authority selectable
	Watchdog	software watchdog
	Recovery	Auto-Reboot
	CMS	YES
Mechanism	IR Remote Controller	YES
	USB Port	2
	Power Supply	DC12V
	Dimension	188mm (W) x 54mm (H) x 209mm (D)
	Operating Environment	30 ~ 80% RH, 5°C~ 40°C(41°F~ 104°F)