

1.0 Megapixel CMOS Waterproof cloud IP Camera

1. Application



IPC ----- Client
 IPC ----- NVR/HVR
 IPC ----- NVR/HVR ----- CMS Client
 IPC ----- MYEYE ----- PC and mobile



2. Specification

model	SST-LPW-PLOGIC
image sensor	1/4" OV OV9712 CMOS
Video standard	PAL/NTSC
min.illumination	Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR black/white 0.2 Lux @ (F1.8,AGC ON),0 LUX with IR
shutter	1/50(1/60)s - 1/10,000 s
lens	HD professional lens 6mm@F1.8(4.2mm,8mm,12mm)
lens mount	CS
adjust angle	Horizontal:0°~355°; Vertical:0°~ 75°
day/night	Support IR-CUT
compression	
video	H.264 HighProfile, JPEG snapshot
bite rate	32 Kbps~8Mbps
max.image	1280×720
frame rate	50Hz:25fps (1280*720),60Hz:30fps (1280*720)
image setting	Saturation, brightness and contrast are adjustable through IE browser or client
network	
storage	network storage
intelligent alarm	Motion detection, video loss, cable break, IP address conflicts
protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP(HTTPS,SIP ,802.1x,IPv6)
basic	anti-flicker, dual-stream, heartbeat, password protection
interface	
net interface	One RJ45 10M/100M
general	

Operating	-10°C~60°C , humidity less than 90%(non-condensing)
power supply	DC12V±10%
Protection	IP66
IR distance	15-30 meters
Dimension(mm)	94*63
weight	250g

