H.264 Video Server (960H)


SST-YES-VSERXL

FEATURES



SST-YES-VSERXL

- ¼H.264, MPEG4, M-JPEG Video Compression
- ¼Resolution up to 960H
- ¼Meets RoHS Directive
- ¼Support LAN & WAN (PPPoE)
- ¼Support Triple Streaming
- ¼Digital Time Code Embedded
- ¼Motion Detection
- ¼Isolated Digital Input and Output Supported
- ¼Two-way Audio



Tol:±0.5 Unit:mm

SPECIFICATIONS

	SST-YES-VSERXL	
TV System	PAL	NTSC
Video Compression	H.264. MPEG4, M-JPG	
Video Frame Rate	25 fps@960x576	30 fps@960 x480
Max. ResoluΘon	960H	
Browser	IE 8.0 or Above	
Ethernet	10/100M Auto Negotiation	
Bit Rate Transmission	64 up to 12,000 Kbps	
Supported Protocols	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DHCP, PPPoE, ARP, UPnP, RTSP, RTP, SNMP, TRAP, Ethernet (RJ-45 Wired 10/100 Base-TX)	
Video Streaming	H.264, MPEG4 and M-JPEG Dual/Triple Streaming	
Audio Streaming	Two-way Audio ; G.711 (μLaw), 8KHz/16KHz Sample Rate	
Users	Support 9 Users	
Security	ID/Password Protection	
Geneal FuncΘon	DI/DO Event Triggered via Ethernet ; Built-in Web Server & Network Interface	
Alarm Trigger	File Upload via FTP and Email/Notification via Email, HTTP, External Digital Output Activation, micro SD Recording	
MulΘcast	Support Multicast Function	
Serial Port	Terminal Blocks (RS-485)	
Analog Video Input	Compositex1, F/BNC Connector	
Analog Video Output	Compositex1, F/BNC Connector	
Audio Input	1.4 Vp-p, 1Vrms, 3.5 mm Jack	
Audio Ouput	1.4 Vp-p, 1Vrms, 3.5 mm Jack	
DI/DO	DIx1 ; DOx1	
Power Supply	12Vdc/PoE	
ConsumpΘon	4.0W	
OperaΘon Temperature	-10°C~50°C	
Storage Temperature	RH80%	
Storage Humidity	-20°C~60°C	
Dimensions	124(W)x43(H)x100(D)mm	
Net Weight	350g	