

POE5912

Features:

- Network devices at Gigabit speeds all within a compact device
- Automatically detects PoE terminals and supplies inline power
- Easily install non-PoE devices where a power outlet is not available
- Reduce installation and network equipment costs
- Safeguards network device with short circuit protection
- Adjustable output DIP switch for 5V, 9V, and 12V adjustable output
- Converts Non-PoE devices with Power Over Ethernet Support
- Auto-sensing power drawn from 802.3af power source equipment(PSE) devices
- Supplies power up to 12.9 watts
- Provides Interchangeable tips

Specification:

Standards Compliance	IEEE 802.3 10Base-T Ethernet
	IEEE 802.3u 100Base-Tx Fast Ethernet
	IEEE 802.3af Power over Ethernet
Data Rate:	RJ-45, 10/100/1000 Mbps
Diagnostic LEDs	DC Power (Green)
Input Power Requirement	Pin Assignment and Polarity: 1/2(+), 3/6 (-) or 4/5(+), 7/8(-)
Output Power Voltage	5V (2A), 9V (1.1A), 12V (0.85A)
others	Compliance RoHS Compliant , CE
	Safety Approvals EN 60950:2006
Warranty	1-year
Dimensions	80mm x 55mm x 31mm (3.14 in x 2.16 in x1.22 in) / 76g (0.16 lbs)
Weight	350g
Environmental Conditions :	Operating Temperature: 0~45°C
	Storage Temperature:95%, Non-condesing