

| Model Number | SST-WPL-CREW | |
|-----------------------|---|-----------------------------------|
| Horizontal Resolution | 5.0MP | |
| Sensor Chip | 1/2.9 CMOS | |
| Image Sensor+DSP | NVP2560+2048 | |
| Effective Pixels | | PAL:25fps |
| | NSTC:30fps | |
| Signal System | PAL/NSTC | |
| Infrared Led | 36 pcs | |
| Infrared Ray Distance | 25-40M | |
| Lens Mount | 3.6mm,6mm,8mm optical focusable MP Lens | |
| Synchronizing System | Internal | |
| Minimum Illumination | Color 0.01 Lux B/W 0.001 Lux (F1.2, AGC ON) 0 Lux with IR | |
| S/N Ratio | More 50 dB (AGC OFF) | |
| Electronic Shutter | 1-1/50 (1~1/60) ~100,000 | |
| Video Output | 1 CH Video Output,Support CVBS, AHD,TVI | |
| OSD Menu | White Balance | ATW/WTW-SET/Manual/Indoor/Outdoor |
| | Backlight Compensation | OFF/HSBLC/BLC |
| | Exposure Mode | Shutter/AGC/DWDR |
| | Day/Night | Auto/Color/Exit/B/W |
| Special | Cam Title/Motion/Privacy | ON/OFF |
| | D-Effect | Freeze/Mirror/Neg Image |
| | Language | More than Ten Different Lauguages |
| | RS485 | Cam ID/ ID Display |
| Adjust | Shutter | Auto/Manual |
| | AGD/Sens-up/Brightness | YES |
| | De-Fog | OFF/Auto |
| Dimension/Weight | 75*75*235(mm)/ 0.5 KG | |
| Material/Color | Aluminum /white | |
| Power Supply | DC 12V. 1A | |
| Operating Temperature | -20°~60° | |