

IP CCTV / Professional IP cameras / Safire Smart / Bullet Cameras

SF-IPB070A-4B1-DL

SAFIRE SMART



Features

- Safire Smart
- B1
- Bullet IP camera
- 1/3" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0 Lux
- Dual light: IR and white light range 20 m
- Compression H.265+ / H.264+
- DWDR
- 3DNR
- Integrated microphone
- Smart Motion Detection: Human motion detection filtering out false alarms
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)
- Weatherproof IP67

Specifications

Brand	Safire Smart
Range	B1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Minimum illumination	Colour: 0.009 Lux @(F2.2, AGC ON), 0 Lux with illumination on
Scope of illumination	Dual lighting: IR up to 20m White LED up to 20m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/3~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 3Mpx, 1080P, 720P)
Extra Stream rate	25 FPS (720P, D1, CIF)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265 / H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 98°, V: 53°, D: 116°
Range performance	56 m (D), 22 m (O), 11 m (R), 5 m (I)
Image improvements	DWDR, BLC, HLC, 3D-DNR, AWB, ROI, ROI, Mirror function, Privacy masking, ROI
Advanced motion detection	Smart Motion Detection: Human-based motion detection filtering out any other objects in the scene
Smart Features	Area intrusion, Line crossing, abandoned object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	Integrated microphone
Audio compression	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	Does not have
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS

Interoperability	ONVIF
Power	DC 12 V / 292 mA / 5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Plastic
Temp. operation	-20° C ~ +55° C
Dimensions	162.1 (D) x 74.8 (W) x 82.8 (H) mm
Weight	250 g