

CCTV IP / Professional IP cameras

## SF-IPD040-4B1

### SF-IPD040-4B1

---

#### Entry-Level B1 IP camera range

Safire's budget series of IP cameras offer features at a very competitive price point that can perfectly cover any basic or entry-level installation. The cameras in this range are available in 2MP and 4MP, have cyber security and VCA functions, which allows for line crossings and area intrusion. In addition, depending on the camera, they have NightColor, Dual Light, IR and white light sensor that can be adjusted according to the customer's preference.

- Dome IP camera range B1 economic
- Resolution 4 Megapixel (2566x1440)
- Lens 2.8 mm | IR 30m
- VCA Rules
- Waterproofing IP67 & IK10 | PoE (IEEE802.3af)



## Technical Specification

### Camera

<b>Image Sensor</b>	1 / 3 "CMOS
<b>Image Size</b>	2560×1440
<b>Electronic Shutter</b>	1 / 3s ~ 1 / 100000s
<b>Iris Type</b>	Fixed Iris
<b>Min. Illumination</b>	0.03 lux @F1.6, AGC ON; 0 lux with IR
<b>Lens</b>	2.8mm@F1.6, Horizontal FoV: 98°;Vertical FoV:53°;Diagonal FoV:116° 3.6mm@F1.6, Horizontal FoV:80°;Vertical FoV:44°;Diagonal FoV:94°
<b>Focus</b>	Fixed
<b>Lens Mount</b>	M12
<b>Day&amp;Night</b>	ICR
<b>Wide Dynamic Range</b>	Digital WDR
<b>BLC</b>	Yes
<b>HLC</b>	Yes
<b>Digital NR</b>	Yes
<b>S/N Ratio</b>	≥50dB
<b>Angle Adjustment</b>	Pan: 0°~355°; Tilt:0°~70°;Rotation: 0°~355°

### Image

<b>Video Compression</b>	Main stream: H.265 / H.264 Sub stream: H.265 / H.264 / MJPEG Third stream: H.265 / H.264 / MJPEG
<b>H.265 Compression Standard</b>	Main Profile@Leve4.1 High Tier
<b>Resolution</b>	4MP ( 2560 × 1440 ), 3MP ( 2304 × 1296 ), 1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1, 480×240, CIF
<b>Main Stream</b>	60Hz: 4MP/3MP/1080P/720P(1~30fps); 50Hz: 4MP/3MP/1080P/720P(1~25fps)
<b>Sub Stream</b>	60Hz: 720P/D1/CIF (1~30fps);50Hz: 720P/D1/CIF (1~25fps)
<b>Third Stream</b>	60Hz: D1/480× 240/CIF (1~30fps);50Hz: D1/480× 240/CIF(1~25fps)
<b>Bit Rate</b>	64 Kbps ~ 8 Mbps
<b>Bit Rate Type</b>	VBR / CBR
<b>Audio Compression</b>	G711A / U
<b>Image Settings</b>	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
<b>ROI</b>	Each ROI to be configured separately

## Interfaces

Network	RJ45
Video Output	No
Audio	No
Storage	No
Reset	No

## Functions

Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP
Web Browser	IE 11 (plug-in required)/Chrome 89.0+/Edge 89.0+/Firefox 87.0+/Safari 14.0+
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion detection
Smart Event	Region intrusion detection, line crossing detection, abandoned/missing object detection, video exception (scene change, video blur and video cast detection)
General Function	Watermark, video mask, heartbeat, corridor pattern
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/HTTPS
IR Distance	20~30m
Ingress Protection	IP 67 & IK10
PoE	Yes, IEEE802.3af

## Intelligent Analytics (Smart Events)

Perimeter Detection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)
Statistics	Target counting by line/area, heat map
Exception Detection	Scene change, video blur and abnormal color detection
Face Detection	Face detection and face capture
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature
Other Events	Abandoned/missing object detection

## DORI Distance

Lens	2.8mm   3.6mm
Detect	56.52m(185.43ft)   71.28m(233.85ft)

<b>Observe</b>	22.61m(74.17ft)   28.51m(93.53ft)
<b>Recognize</b>	11.30m(37.07ft)   14.26m(46.78ft)
<b>Identify</b>	5.65m(18.53ft)   7.13m(23.39ft)

## Others

<b>Power Supply</b>	DC12V/PoE
<b>Power Consumption</b>	< 4W
<b>Storage Conditions</b>	- 30 °C ~ 60 °C (-22°F~140°F);Humidity: less than 95 % (non-condensing)
<b>Operating Conditions</b>	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
<b>Dimensions ( mm )</b>	Ø 110× 83.3
<b>Weight ( net )</b>	Approx. 0.5KG
<b>Installation</b>	Ceiling mounting ( Wall mounting available with the junction box and bracket )
<b>Certificate</b>	CE, FCC
<b>Environmental Protection</b>	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)