

CCTV IP / Professional IP cameras

SF-IPB580ZA-4B1-DL

SF-IPB080A-4E1

H.265+ ECO Series

The ECO range is the entry level for IP cameras. It stands out for its good night-time performance and Matrix LED illumination system, as well as its characteristic robustness and reliability, which satisfy any standard installation. Efficient H.265+ encoding, which saves 80% in storage and bandwidth over H.264 codec. Power over the POE network cable greatly simplifies installation.

- Bullet IP Camera range E1 Artificial Intelligence
- Resolution 4 Megapixel (2566x1440)
- Lens 2.8 mm | Audio IN | IR 30m
- AI: Classification of human and vehicle
- Waterproofing IP67 | PoE (IEEE802.3af) | P2P



Technical Specification

Camera

Image Sensor	1 / 3 "CMOS
Image Size	2560×1440
Electronic Shutter	1/2s ~ 1 / 100000s
Iris Type	Fixed Iris
Min. Illumination	0.005 lux @F1.6, AGC ON; 0 lux with IR
Lens	2.8mm@F1.6, Horizontal FoV: 94°;Vertical FoV:50°;Diagonal FoV:115° 3.6mm@F1.6, Horizontal FoV:78°;Vertical FoV:40°;Diagonal FoV:97°
Focus	Fixed
Lens Mount	M12
Day&Night	ICR
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Digital NR	Yes
Angle Adjustment	Pan: 0°~360°; Tilt:0°~80°;Rotation: 0°~360°

Image

Video Compression	Main stream: H.265 / H.264 Sub stream: H.265 / H.264 / MJPEG Third stream: H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, 480×240, CIF
Main Stream	60Hz: 4MP/3MP/1080P/720P(1~30fps); 50Hz: 4MP/3MP/1080P/720P(1~25fps)
Sub Stream	60Hz: 720P/D1/CIF (1~30fps);50Hz: 720P/D1/CIF (1~25fps)
Third Stream	60Hz: D1/480× 240/CIF (1~30fps);50Hz: D1/480× 240/CIF(1~25fps)
Bit Rate	64 Kbps ~ 8 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately

Interfaces

Network	RJ45
---------	------

Video Output	No
Audio	1CH audio input
Storage	Built-in micro SD card slot, up to 256GB
Reset	Yes

Functions

Remote Monitoring	Web browser /TVT NVR/NVMS2.X/Mobile APP
Web Browser	IE (plug-in required)/Google Chrome/Edge/Firefox/Safari
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF
P2P	Yes
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, SD card full, SD card error
Smart Event	Video Exception (scene change, video blur and video cast detection), line crossing detection and region intrusion detection
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock,corridor pattern
PoE	Yes
IR Distance	20 ~ 30 m
Ingress Protection	IP67

DORI Distance

Lens	2.8mm 3.6mm
Detect	61.76m(202.62ft) 79.13m(259.61ft)
Observe	24.70m(81.03ft) 31.65m(103.83ft)
Recognize	12.35m(40.51ft) 15.83m(51.93ft)
Identify	6.18m(20.27ft) 7.91m(25.95ft)

Others

Power Supply	DC12V/PoE
Power Consumption	< 5W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F);Humidity: less than 95 % (non-condensing)
Storage Environment	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Dimensions (mm)	167.5 x 74.5 x 74.5
Weight (net)	Approx. 0.38KG

Installation	Ceiling mounting; Wall mounting
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)