



## PoE Cameras Specification :

### Specification :

|                    |   |
|--------------------|---|
| Sensor             | 1/3" OV4689 CMOS For 4MP                              |
| Min illumination   | Color :0.01Lux ; 0 LUX with IR On                     |
| shutter            | 1/50(1/60)s to 1/100, 000s                            |
| lens               | Standard 3.6mm  |
| <b>Compression</b> |   |
| Video              | H. 265 High Profile, support dual stream, AVI format; |

|                   |   |
|-------------------|---|
| compression       |   |
| Video bit rate    | 100Kbps~8Mbps   |
| <b>Image</b>      |   |
| Resolution        | <b>4MP : Main stream:4MP 2560*1440<br/>25fps      sub-stream: 1280*720,704*576 25fps</b>  |
| Frame Rate        | 25fps For 4MP   |
| Image setting     | Saturation, brightness,<br>contrast can be adjusted via client side or IE browser   |
| <b>Network</b>    |   |
| Storage           | Via PC/Mobile Phone/NVR With HDD  |
| Intelligent alarm | Motion detect, video lost, network break, IP conflict,<br>storage device full or error  |
| Protocol          | 1 * RJ45, 10/100M; Support TCP/IP<br>HTTP/RTSP/FTP/PPPOE/DHCP/DNS/DDNS/NTP/UPnP<br>Support WEB remote configuration, OSD, motion detect,<br>alarm input active to record, s |
| Noise Reduction   | Supports 2D/3D  |
| <b>Interface</b>  |   |
| Communicating     | 1pcs RJ45 10M/100M self adaptive Ethernet interface   |
| Video output      | Support overlying DDNS, user name, password and other<br>info.  |
| <b>General</b>    |   |
| Working condition | -20~60 degree. humidity less than 90%(non-condensing)   |
| Power             | 48V POE   |
| Protection level  | High Quality Metal IP67   |