

**AT-XMEYE4****Feature:**

- ▣ Support VGA, HDMI full HD output simultaneously;
- ▣ Support ONVIF; access third party;
- ▣ Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- ▣ Support web, CMS, center platform management software MYEYE, provide SDK development;
- ▣ Support various mobile monitoring (iPhone, Android);
- ▣ Remote Access, With DNS (ARSP),easy to monitor remotely
- ▣ Support UTC, control signal& video stream transmit through one single coaxial
- ▣ Support AHD/TVI/CVI/CVBS/IP five signals;

**Specification:**

	<b>Model</b>	AT-XMEYE4
System	Main processor	Hi3520D V200
Interface	Preview	1/4
Video	Codec	H.264
	Monitor quality	VGA,HDMI: HD
	Preview ability	4*1080N (5 in 1)
	Encode ability	4*1080N (5 in 1)
	Decode ability	1*1080N (5 in 1)
	Multi-mode input	analog: 4*1080N (5 in 1); 4*720P; 4*960H hybrid: 2*720P(analog)+2*720P(network); network: 8*1080P; 12*960P; 8*720P; 4*1080P; 4*720P; 1*1080P
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	4ch BNC
	Video output	1ch VGA, 1ch HDMI, 1ch BNC
	Loop Vout	N/A

	Audio I/O	4/1
	Alarm I/O	0 (Can be extended to 4ch) / 0 (Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Max 8TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃, Humidity:10%—90%, Atm:86kpa—106kpa

	Dimension	254mm*215mm*42mm
	Weight	1.15KG

