

AXIS T91L61 Wall-and-Pole Mount

For quick wall and pole installations

Designed for Axis PTZ and multisensor cameras, AXIS T91L61 Wall-and-Pole Mount can quickly connect power and data to the camera through a built-in Ethernet cable with an IP66 RJ45 connector. The ability to choose between an RJ45 or IDC (insulation-displacement contact) connector makes installation flexible. AXIS T91L61 is also suitable for corner mounting with an optional accessory. Thanks to its impact-resistant and outdoor-proven material, it can be used in both indoor and outdoor environments. Note that this mount is not intended for inverted installations.

- > **Flexible installation using the IDC connector**
- > **Built-in IP66 RJ45 connector**
- > **Suitable for wall and pole mounting**
- > **Protection against impact, water, dust and corrosion**



AXIS T91L61 Wall-and-Pole Mount

General	
Supported products	AXIS Q60 Series AXIS Q61 Series AXIS P55 Series AXIS P56 Series AXIS Q37 Series
Casing	Material: Powder-coated aluminum casing Color: White NCS S 1002-B
Sustainability	PVC free
Connectors	Out: IP66 RJ45 Ethernet (male) In: RJ45 Ethernet (female), IDC
Environment	Indoor Outdoor
Operating conditions	-50 °C to 65 °C (-58 °F to 149 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	Safety IEC/EN/UL 60950-1, IEC/EN/UL 60950-22 Environment IEC 60721, IEC 60721-4 Class 4M3, MIL-STD 810G 509.5, IP66, NEMA 250 Type 4X, RoHS, WEEE
	Impact IEC 62262 IK10
Dimensions	280 x 174 x 152 mm (11 x 7 x 6 in)
Weight	1.85 kg (4 lb)
Maximum load	30 kg (66 lb)
Cable routing	Back: Cable hole Bottom: 3/4" Conduit entrance
Included accessories	Installation Guide
Optional accessories	AXIS ACI Conduit Adapters AXIS T91A64 Corner Bracket AXIS Steel Straps TX30 570 mm AXIS Steel Straps TX30 1450 mm For more accessories, see www.axis.com
Warranty	3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility