

AXIS M4206-V Network Camera

Varifocal mini dome with HDMI

AXIS M4206-V Network Camera delivers clear, sharp video surveillance in difficult light conditions whether you need hawk-eye overviews or detailed close-ups. The ultra-compact and dust-resistant casing is designed to blend seamlessly into any indoor environment. AXIS M4206-V only requires two screws to mount on ceiling or wall, and the camera features a varifocal lens that can be adjusted from a remote location. With over 40% recycled plastics, AXIS M4206-V is designed for flexible, cost-effective and environment-friendly installations.

- > **3 MP/HDTV 1080p**
- > **Varifocal lens with remote zoom and focus**
- > **WDR for difficult light conditions**
- > **Zipstream with H.264 and H.265**
- > **HDMI output for public monitors**



AXIS M4206-V Network Camera

Camera	
Image sensor	1/2.5" progressive scan RGB CMOS
Lens	Varifocal, 3–6 mm, F2.0 Horizontal field of view: 100°–45° Vertical field of view: 72°–34° Remote focus and zoom, fixed iris
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.26 lux at 50 IRE F2.0 B/W: 0.05 lux at 50 IRE F2.0
Shutter speed	1/10000 s to 1/5 s
Camera angle adjustment	Pan ±180°, tilt -40 to +65°, rotation ±105° Can be directed in any direction and see the wall/ceiling
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main and High Profiles Motion JPEG
Resolution	2048x1536 to 320x240
Frame rate	25/30 fps with power line frequency 50/60 Hz
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265 HDMI
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate streaming
HDMI output	HDMI 1080p (16:9) @25/30 fps (50/60 Hz) HDMI 720p (16:9) @50/60 fps (50/60 Hz)
Image settings	Compression, color, brightness, sharpness, contrast, white balance, exposure control, WDR: up to 110 dB depending on scene, text and image overlay, mirroring of images, privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format
Pan/Tilt/Zoom	Digital PTZ
Network	
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware
Supported protocols	IPv4, IPv6, USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI, LLDP, MQTT v3.1.1
System integration	
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org
Event triggers	Analytics, edge storage events, virtual inputs through API
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text
Data streaming	Event data
Built-in installation aids	Remote zoom, remote focus, pixel counter
Analytics	
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard Supported AXIS Video Motion Detection

AXIS People Counter, AXIS Occupancy Estimator, AXIS Direction Detector, AXIS Tailgating Detector, AXIS Random Selector, AXIS Queue Monitor
Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap

General	
Casing	IP42 water- and dust-resistant, IK08 impact-resistant, polycarbonate and aluminum casing with hard-coated dome (to comply with IP42, follow Installation Guide) Encapsulated electronics Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.
Sustainability	PVC free, 43% recycled plastics
Memory	512 MB RAM, 512 MB Flash
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 3.2 W, max 4.6 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE HDMI type D
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Operating conditions	0 °C to 45 °C (32 °F to 113 °F) Humidity 10–85% RH (non-condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, EN 55024, EN 61000-6-1, EN 61000-6-2, IEC 62236-4, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1, IS 13252 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60529 IP42, IEC/EN 62262 IK08 Network NIST SP500-267
Dimensions	Height: 71 mm (2.8 in) ø 121 mm (4.76 in)
Weight	350 g (0.77 lb)
Included accessories	Installation guide, Windows [®] decoder 1-user license
Optional accessories	AXIS T94C01L Recessed Mount AXIS T94C01U Universal Mount AXIS T94C01M J-Box/Gang Box Plate AXIS M42 Casing A Black 4P AXIS M42 Smoked Dome A 4P AXIS T91A33 Lighting Track Mount AXIS T91A23 Tile Grid Ceiling Mount AXIS TM3101 Pendant Wall Mount AXIS Surveillance Cards For more accessories, see axis.com
Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Japanese, Korean, Portuguese, Simplified Chinese, Traditional Chinese
Warranty	5-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility