



- * Support 4 ch 1080P Network Video Input ; 4 POE ports Support POE power supply;
- * Support VGA, HDMI 1080P full HD output simultaneously;
- * Support ONVIF;Support Third-party network cameras ;
- * Support Web, CMS, platform management software XMEYE,Provide SDK ;
- * Support cloud service, network penetration, alarm information pushed to phone ,etc;
- * Support multiple network services like DHCP, FTP, DNS, DDNS, NTP,UPNP, EMAIL,3G,WIFI, IP searches, Alarm Center, etc.

Specification :

Model	NVR-3104PL/POE	
System	Main processor	Industrial-grade embedded HiSilicon CPU

	Operating System	Embedded Linux
	System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4 split screen
Video	Video input (IP)	4*1080P
	Video standards	PAL(625TVL,50f/s) ; NTSC(525TVL,60f/s)
	Video compression	H.264
	Display quality	Max 1920*1080
	Playback quality	1*1080P
	Decode	1*1080P
	Motion detection	Support(depend on camera)
Audio	Audio compression	G.711A
	Intercom	Unsupport
Record & playback	Recording mode	Manual>Alarm>Dynamic Detection>Timing
	Local playback	1*1080P
	Search mode	Search by Time/Calendar/Event/Channel
Storage & Backup	Space occupation	Video : CIF 4~5G/day*channel , D1 8~10G/day*channel ; 960H 12G~20G/day*channel 720P 20~30G/day*channel ; 1080P ~40G/day*channel ; Audio : 691.2M/day*channel
	Record storage	HDD、 Network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	Video output	1ch HDMI,1chVGA Full HD output
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
		4 POE ports Support POE power supply
	POE power supply distance	100m
	USB interface	2*USB2.0 ports
	HDD	1 SATA
General	PTZ control	Control PTZ device by network

	ONVIF	Support
	Power supply	48V1.5A
	Power Consumption	<32W(Without HDD)
	Work environment	Temperature:0°C- + 55°C , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Dimension	255*50*220mm
	Weight	2KG